

BEADLESS LITE FLUSH DOOR

Resulting from a dedication to artistic craftsmanship, state-of-the-art technology, and a passion for innovation, Eggers' beadless lite flush door offers clean lines, a streamlined design and a modern touch to any project.



Eggers Industries



| ENGINEERING SPECIFICATIONS | | BEADLESS LITE FLUSH DOOR | |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|------------------------------------------------------------------------------------------|
| | 20-Minute Single | 20-Minute Pairs | Non-Rated |
| Max. Size | 4' x 10' | 8' x 10' parallel and dbl. egress | 4' x 10' (per leaf) |
| Thickness | 1-3/4" - 2-1/4" | | |
| Core | Particleboard, UF-free particleboard, FSC® certified particleboard, Stave, FSC certified stave, or structural composite lumber (SCL) | | |
| Stiles | Veneered structural composite lumber, solid lumber edges available upon request | | |
| Rails | No-Rail construction is standard for SCL; 1-1/8" for all other core types (multiple-ply optional) | | |
| Reinforcements | Not required for extra heavy duty applications for SCL and stave core | | |
| Faces | All available domestic and foreign veneers, medium density overlay (MDO) and vinyl | | |
| Crossbands | 1/11" high density fiberboard | | |
| Lites | Up to 1296 sq. in. standard, SCL, and stave core available with 2868 sq. in. Maximum 6" top rail; factory glazing required. | | Size restricted only by min. margins Maximum 6" top rail; factory glazing required |
| Latching Hardware | Cylinders, mortised, unit, or card locks; 5" backset and deadbolts available | | Most available latching hardware |
| Hinges | Per NFPA 80 - butts, pocket pivots, continuous hinges, pivots (electrical options available) | | |
| Flushbolts | N/A | Automatic corner or extension bolts up to 36" | Corner or extension bolts up to 48" |
| Exit Hardware | Rim, surface vertical rod (full or top rod only), and fire exit hardware | | |
| Closers, Stops, Holders | Listed surface hardware | | |
| Drop Seals | Listed and approved surface, semi-mortised or mortised | | |
| Special Details | Machining for hardware; installation of lites; sketch faces; applied moulding; kickplates; reveals; solid grillwork and divided lites | | |
| Finish | UV-cured, primed, sealer, full sealer, catalyzed polyurethane and opaque varnish | | |
| Warranty | Life of installation - not suitable for exterior installation | | |
| Standards | WDMA I.S. 1A, AWI Section 1300 8th Edition, NFPA 252, UL 10C, NFPA 80 | | |



**Stile & Rail Doors,
Door Frames, Plywood,
Veneered Components**

Two Rivers Division
One Eggers Drive
Two Rivers, WI 54241
Phone: 920.793.1351
Fax: 920.793.2958

www.eggiersindustries.com

Flush

Neenah Division
164 North Lake Street
Neenah, WI 54956
Phone: 920.722.6444
Fax: 920.722.0357

email: sales@eggiersindustries.com

Eggers releases regular product updates. Please visit www.eggiersindustries.com for the most current and accurate technical information. Specification details published online supersede those in print.

The FSC® certification ensures responsible use of forest products. 04-12
Look for FSC certified products.

