

# ACOUSTIC GASKET SYSTEMS

Installation Instruction 124



Eggers Industries

Date: February, 2015

## Installation of Perimeter Seals: Gasket System R

1. Install the Zero 369 door bottom in accordance with the manufacturer's instructions prior to hanging the door.
2. Turn the adjustment screw on the door bottom in so that the seal will not activate when the door is closed.
3. Hang the door and adjust for proper clearances.
4. Prepare the frame by cleaning the jamb, header and stops where the frame seals will be applied.
5. Measure, cut and apply the Zero 8145S gasket on the frame jamb and header, adjacent to the stop. Trim the ends where they meet in the corners such that a good seal will be maintained when the door is in the closed position. The Zero 8145S should be full height or width of the opening and should not be spliced.
6. Measure, cut and apply the Zero 119W gasket on the frame jamb and header. This seal should be located adjacent to the pull face of the frame. Trim the ends where they meet in the corners such that a good seal will be maintained when the door is in the closed position. The Zero 119W should be full height or width of the opening and should not be spliced.
7. Turn the adjustment screw on the door bottom out to the point where the seal makes uniform firm contact with the sill when the door is closed. If a flat threshold is being used a sealant, such as silicone caulk, should be used to prevent sound transmission between the threshold and floor. Door bottoms should not be used over carpeted sills as this will not provide a good seal.



Stile and Rail Doors,  
Door Frames, Plywood  
Veneered Components

Two Rivers Division  
One Eggers Drive  
Two Rivers, WI 54241  
Phone: 920.793.1351  
Fax: 920.793.2958

Flush Doors

Neenah Division  
164 North Lake Street  
Neenah, WI 54956  
Phone: 920.722.6444  
Fax: 920.722.0357

Architectural Veneer Faces,  
Custom Wood Products,  
Plywood

Kentucky Division  
2125 Lake Jericho Road  
Smithfield, KY 40068  
Phone: 502.845.0154  
Fax: 502.849.0444