



Stile & Rail Doors, Door Frames,
Veneered Components, Plywood

Two Rivers Division
One Eggers Drive
Two Rivers, WI 54241
Phone: 920.793.1351
Fax: 920.793.2958
email: sales@eggersindustries.com

Flush Doors

Neenah Division
164 North Lake Street
Neenah, WI 54956
Phone: 920.722.6444
Fax: 920.722.0357

REQUEST FOR QUOTATION

Distributor Name: _____
 Requested By: _____
 Phone: _____
 Fax#: _____
 E-Mail: _____
 To: _____
 Bid Date / Time: _____
 Job Name: _____
 Job Location: _____
 Delivery Date: _____

Coordination By

Distributor
 Eggers

Customer Type

Distributor/Subcontractor
 Millworker
 General Contractor
 Facility Manager
 Material Supplier
 Other

Packaging

Polybag Cardboard
 Sort by Floor

Louvers

Non-Rated Door:

C/O Only
 Oval Slat
 V-Slat
 Non-Vented

Rated Door:

C/O Only
 Metal Fusible Link

Glazing

By Eggers
 By Others

PB (Particleboard) SHC (Std. Hollow Core) M45 (Mineral 3/4 Hour C)
 SCLC (Structural Composite Lumber Core) STC (Acoustical - Specify Rating) M60 (Mineral 1 Hour B)
 SLC (Stave Lumber Core) LL (Lead Lined - Specify Thickness) M90 (Mineral 1-1/2 Hour B)

Vinyl Faced Doors


Pattern: Solid Woodland

Material: IPC Rigid PVC EnviroGT Rigid Non-PVC (solid colors only)

Finish: Textured (Standard) Smooth (option-note slightly extended lead times)

Environmental Requirements	Fire Rated Doors	
<input type="checkbox"/> No Added Urea Formaldehyde	<input type="checkbox"/> Neutral Pressure	<input type="checkbox"/> Hollow Metal Frames
<input type="checkbox"/> Recycled Content	<input type="checkbox"/> Positive Pressure Category A	<input type="checkbox"/> Rated Aluminum Frames
<input type="checkbox"/> Rapidly Renewable Materials	<input type="checkbox"/> Positive Pressure Category B	
Vertical Edges		
<input type="checkbox"/> Fixed		
<input type="checkbox"/> Removable		
WDMA Performance Standard	Note: Eggers Industries uses only LD-2 board for particle core doors.	
<input type="checkbox"/> Standard Duty	This core meets the performance requirements of WDMA I.S. 1A-04	
<input type="checkbox"/> Heavy Duty	Heavy Duty, including screw withdrawal through the face. Blocking	
<input type="checkbox"/> Extra Heavy Duty	is no longer required for screw-attached surface mounted hardware.	

Note:
All doors are 1-3/4" thick unless otherwise stated under 'Other Information/Special Construction.'



Light Openings

Non-Rated

C/O Only Std. Flush Wood Bead
 MVP Std. Lip Wood Bead

Rated

C/O Only Veneer Wrapped Bead
 MVP

Glass Type

N/R Type _____
 20 Min Type _____
 45-90 Min Type _____

Item #	Total Door Qty.	Pair Match	Double Egress	Core/Rating	SIZE Width x Height (list in feet)	Lite/Louver Cut Out Size or Pattern	Hinge	Cylinder/Mortised Lock	Strike & Flush Bolts	Rim Panic	SVR	Mortised Exit Device	CVR	Top Blocking	1 or 2 Lockblock	Bottom Blocking	Miscellaneous
1					X												
2					X												
3					X												
4					X												
5					X												
6					X												
7					X												
8					X												
9					X												
10					X												

continued on page 2

REQUEST FOR QUOTATION - Page 2

Item #	Total Door Qty.	Pair Match	Double Egress	Core/Rating	SIZE Width x Height (list in feet)	Lite/Louver Cut Out Size or Pattern	Hinge	Cylinder/Mortised Lock	Strike & Flush Bolts	Rim Panic	SVR	Mortised Exit Device	CVR	Top Blocking	1 or 2 Lockblock	Bottom Blocking	Miscellaneous
11					X												
12					X												
13					X												
14					X												
15					X												
16					X												
17					X												
18					X												
19					X												
20					X												
21					X												
22					X												
23					X												
24					X												
25					X												
26					X												
27					X												
28					X												
29					X												
30					X												
31					X												
32					X												
33					X												
34					X												
35					X												
36					X												
37					X												
38					X												
39					X												
40					X												

_____ Total Leaves

Other Information/Special Construction _____